

**PRODUCT : Cloth Tape #400**

**BRAND :**   
*Pressure Sensitive Tapes*

**ORIGIN : Made in Korea**

## **SPECIFICATION**

### **DESCRIPTION**

- \* Polycloth adhesive tape

### **ADHESIVE**

- \* Coated with Vacuum hotmelt adhesive ( Synthetic Rubber )
- \* Woven 70 mesh
- \* Tolerance :  $\pm 1$  mesh

### **CARRIER**

- \* Woven polyester and cotton-coated, blended with LDPE

### **APPLICATIONS**

- \* Sealing and insulating applications
- \* Hole closure, repairing and masking
- \* Interior and exterior use
- \* Packaging, holding and bundling

### **COLOUR**

Beige, Red, D.Blue, L.Blue, Green, Yellow, White, Silver, Black, Brown, Pink and Orange

### **TECHNICAL DETAILS**

Total thickness -----	0.25 $\pm$ 0.01mm
Adhesive to steel -----	> 65 oz/in
Tensile Strength -----	> 14.3 lb/in
Rolling ball tack -----	> 10 (Ball no.)
Elongation -----	15 - 25%
Holding power -----	N/A
Service temperature range -----	- 15°C - > + 70°C

### **APPLICATION**

Temperature : between 0°C and + 35°C. Surface must be clean and free from dust and grease. Avoid touching the tapes exposed adhesive surface in order to keep full adhesive performance. Pressure sensitive adhesive must be applied with a maximum of pressure in order to achieve maximum pressure level. The indicated level of performance will be reached after a bonding period of 24 HRS at 23°C.