

# NOISE REDUCTION. ALL DAY COMFORT.



ATTENUATION DATA								
Frequency [Hz]	63	125	250	500	1000	2000	4000	8000
Sound Attenuation [dB]	24.1	29.4	33.9	36.6	35.5	35.8	45.1	45.7
Standard Deviation [dB]	4.6	5.2	5.9	6.4	5.9	3.9	3.6	5.7
Assumed Protection (APV) [dB]	19.5	24.2	28.0	30.2	29.6	31.9	41.5	40.0

\*SNR = 34dB    H = 34dB    M = 31dB    L = 29dB



**Resealable Packaging**  
Secured Storage

**Expands Quickly**  
Easy Usage

**Soft Foam**  
All Day Comfort

**Tapered Shape**  
Better Fitment

**High SNR**  
Reduce Noise Effectively

### SPECIFICATIONS

Material	Polyurethane
Design	Bullet Model
Texture	Smooth and Soft
Single Number Rating (SNR)	34dB
Colour	Yellow

### RECOMMENDED APPLICATIONS

- Light and Precision Engineering
- Assembly and Maintenance
- Grinding and Angle Grinding
- Offshoring/Maritime
- Oil and Gas
- Plant Visitors

### CARE INSTRUCTIONS

Inspect- Prior to fitting, discard if earplug is dirty, damaged, hard or stiff.  
Hygiene- To maintain hygiene, discard disposable earplugs at the end of every shift.

### PACKING DETAILS

Selling Unit	1 Bag of 100 Pieces
Outer Carton	20 Bags
Carton Size	52.5CM x 42.5CM x 40.5CM
Volume	0.0904CBM
Gross Weight	10KG

**EVO**  
**FULL**  
**RANGE**

